

Guidelines for MI60 Extraction with Three Kickers

Dave Johnson
May 18, 2002

Assume all three kickers are downstream of Q602
 Assume current instrumentation can be relocated
 Assume downstream end of third kicker is ~ 7.5 meters downstream Q602
 Vertical aperture of 3rd kicker must not be limiting aperture
 Vertical design beta at QD location ~ 55 meters
 Vertical ID of MI beam pipe ~ 1.88 " (47.75 mm)
 Vertical beta at downstream end 3rd kicker ~ 25 meters
Minimum vertical aperture of 3rd kicker beampipe
 $1.88'' * \text{sqrt}(25/55) \Rightarrow 1.27''$ (**32 mm**)

Vertical Acceptance of MI at 8 GeV: Use $\pm 4 \sigma$ to determine acceptance
 $47.75 \text{ mm} / 8 \Rightarrow \sigma = 5.97 \text{ mm}$
 Acceptance = $6(\gamma\beta)\sigma^2 / \beta \Rightarrow 36.8 \pi\text{-mm-mr} \sim \mathbf{40 \pi\text{-mm-mr}}$
If use $\pm 2.45 \sigma \Rightarrow 95 \pi\text{-mm-mr}$

Currently on stacking cycles $\epsilon_H \sim 1.5 * \epsilon_V$ ($\epsilon_V \sim 15 \pi\text{-mm-mr}$)

Horizontal Acceptance limited by field free aperture in Lambertson.
 $W \sim \text{MI beam pipe width}/2 \Rightarrow 60 \text{ mm}$
 Acceptance = $6(\gamma\beta)\sigma^2 / \beta \Rightarrow 58 \pi\text{-mm-mr} \sim \mathbf{60 \pi\text{-mm-mr}}$

Assume blow up beam emittance in each plane by factor 2 at 120 GeV, the emittance at 120 GeV to determine apertures should be

$$\epsilon_H \Rightarrow \mathbf{120 \pi\text{-mm-mr}}$$

$$\epsilon_V \Rightarrow \mathbf{60 \pi\text{-mm-mr}}$$
